

## MINI-SQ SERIES

### SQUARE LED EMERGENCY LIGHT WITH NICAD BATTERY



#### OVERVIEW

Our MINI-SQ emergency light is one of the most compact and efficient emergency light available today. A nickel-cadmium battery provides emergency power illumination to (2) LED emergency lamps. The LED lamps require 1/4 the electrical power of standard emergency lights, reducing the size of the unit and improving the maintenance profile.

The square-shaped LED emergency lamps last for up to 100,000 hours and the Ni-Cad emergency light battery lasts for 5-7 years.

The MINI-SQ emergency light is constructed from white thermoplastic and features adjustable lamp heads that are gyroscopically mounted for easy positioning. The MINI-SQ emergency light surface mounts to normally inflammable ceilings and walls.

A simple push button allows easy testing of the emergency light's Ni-Cad emergency light battery. The MINI-SQ emergency light is UL Listed and comes complete with a five-year warranty.

#### EXTERNAL SPECIFICATIONS

The MINI-SQ emergency light is constructed from flame and corrosion resistant ABS thermoplastic. The housing comes standard in white, and is also available in black.

The lamps are easy to adjust and are gyroscopically mounted so they can be positioned at the most ideal angle for illuminating the path of egress.

#### LED LAMP SPECIFICATIONS

The LED lamps for this emergency light use less than 3 watts of electricity to produce the same illumination levels as a standard 5.4 watt incandescent emergency lamp.

#### LED SPECIFICATIONS

- **Lamp Type:** LED
- **Lamp Shape:** Square
- **Lamp Wattage:** 1.15W
- **Color Temperature:** 5000K
- **Lifespan:** 50,000+ Hours

## ELECTRICAL SPECIFICATIONS

120/277V AC dual-voltage operation is standard. Other voltages available upon request such as 220V, 240V, and 480V.

## SELF-DIAGNOSTIC TESTING (SDT OPTION)


SDT circuitry continuously monitors every critical function of the unit. Purchase the SDT option to eliminate the requirement of monthly/yearly manual testing of emergency lights/exit signs. SDT meets NFPA 101 Life Safety Code requirements for periodic testing.

## REMOTE CAPABILITY (RC OPTION)

The MINI-SQ Series RC option allows the fixture to operate multiple lamp heads that are located away from the fixture. Utilizing the remote capability option eliminates installation of more individual fixtures and decreases the number of batteries to be maintained.

## BATTERY SPECIFICATIONS

The MINI Series uses a 3.6V Nickel Cadmium emergency light battery. Provides a minimum 90 minutes of emergency power to the (2) MINI Series LED emergency lamps.



## DIMENSIONS

Wattage	A	B	C
1.8 watts	10.5"	3.5"	3.25"

## CODE COMPLIANCE

UL924 Listed for the U.S. and Canada, CS860, NFPA, Life Safety 101, UL Listed for Damp Locations. UL Listed for Damp Locations.



## WARRANTY

This LED emergency light comes with a three-year factory warranty. The lamps are not covered. Deliberate damage, misuse, or improper installation effectively cancel the warranty. Battery features a 20% per year pro-rata warranty.

## ORDERING INFORMATION

Series	Lamp	Housing	Options (may be combined)
MINI-SQ	L (LED)	W (white) B (black)	RC (remote capability) SDT (self-diagnostic testing) CS10 (10-foot plug-in cord) 120M (120-minute run time)